



FFS-10000


FAST FUSION SPLICER

PRESENTING THE SPLICING BENCH MARK

PRODUCT HIGHLIGHTS :

- ❖ 6 Motors Core Alignment System
- ❖ Very High Performance Machine
- ❖ Outclass any other make of Fusion Splicer
- ❖ Long Lasting 8500 mAH Battery
- ❖ Smart App- Bluetooth Connectivity and Data Transfer
- ❖ Fast 6 Second Splice 12 Second Heating Time
- ❖ Long Battery - upto 500 splice in one charge
- ❖ Low Maintenance Cost & Economical Spares
- ❖ Highly Resistant to: Dust/Shock/Water
- ❖ Easy for Coupler Splicing


Fast
&
RELIABLE



Fiber Core Identification System
Auto Splicing Mode



12 Sec Fast Heating Time
Super Smart Heater



Ceramic Short V-Groove
Stable & Durable

FAST
1 Sec Start

8400 mAh
SUPER
BATTERY



6 Motor
Core
Alignment

USB
Remote
Support

OUR BRANCHES :

Delhi, Ludhiana, Guwahati, Kolkata, Bhopal, Hyderabad, Mumbai

SPECIFICATIONS

Applicable Fiber	SM(ITU-T G.652/G.657), MM(ITU-T G.651), DS(ITU-T G.653), NZ/NZDS (ITU-T G.655)
Cladding/Coating Diameter	Dia 80~150 μ m, Dia 100~1000 μ m
Cleave Length	250 μ m cladding diameter 8~16mm, over 250 μ m cladding diameter 16mm
Splice/Heating Modes	Max. 100 / Max. 30
Splice Loss	0.02dB (SM), 0.01dB(MM), 0.04dB(DS) and 0.04dB(NZDS) Measured by cut-back method relevant to ITU-T and IEC standards.
Return Loss	>>60dB
Splicing Time / Tube Heating Time	Typical 6sec. with SM / Adjustable, 12sec. typical
Splice Date Storage/Image Capture	Max. 10000 / Max. 100
Viewing Method / Magnification	560x for X or Y single axis view, / 270x for both X and Y dual axis view
Tension Test	1.96~2.25N
Applicable Protection Sleeve	10~60mm
No. of Splice/Heating per Battery Charge	Typical 350 cycles
Electrode Life	5000 arc discharges
Size & Weight	190x140x150(mm), 1.8kg (2.2kg with battery)
Operating Condition	Altitude: 0 to 5,000m above sea level, Wind: 15m/sec, Temperature: -20 to 50deg C, Humidity: 0 to 95%RH, non-dew
Storage Condition	Humidity: 0 to 95%, Temperature -40~+80degC (Battery -20~+40degC)
Resistance Feature	Shock resistance : 76cm (30inch) 5 difference surface drop* Dust resistance : Exposure to dust (0.1 to 500 μ m dia. Alumina Silicate) Rain resistance : H=10mm/hr for 10min
Terminal	High Speed USB
Power Supply	AC 100~240 Volt, 50/60Hz
Battery Module	8400 mAh high capacity battery

STANDARD PACKAGE

Single Fiber Fusion Splicer	High Capacity Battery	AC Adapter	Spare Electrode
Fiber Optic Stripper	User Guide	DC Charging Cable	AC Adapter Cable
Cooling Tray	Shoulder Strap	Hand Strap	Carrying Case

Authorised distributor :

Sales Helpline : +91-9899002699

E-mail: info@starffs.com



www.facebook.com/ffs10000

